

**Safety Data Sheet  
Restor-A-Finish**

Howard Restore A  
Finish Mahogany

SDS Revision Date:

08/20/2014

**1. Identification**

**1.1. Product identifier**

**Product Identity**

Restor-A-Finish

**Alternate Names**

Restor-A-Finish

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Intended use**

See Technical Data Sheet.

**Application Method**

See Technical Data Sheet.

**1.3. Details of the supplier of the safety data sheet**

**Company Name**

Howard Products, Inc.

560 Linne Road

Paso Robles, CA 93446

**Emergency**

**CHEMTREC (USA)**

(800) 424-9300

**Customer Service: Howard Products, Inc.**

EMERGENCY PHONE: 1-805-227-1000

FAX PHONE: 1-805-227-1007

**2. Hazard(s) identification**

**2.1. Classification of the substance or mixture**

Flam. Liq. 2;H225

Highly Flammable liquid and vapor.

Acute Tox. 4;H332

Harmful if inhaled.

Skin Irrit. 3;H316

Causes mild skin irritation. (Not adopted by US OSHA)

Eye Irrit. 2;H319

Causes serious eye irritation.

**2.2. Label elements**

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

### [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

### [Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations                                                   | Weight % | GHS Classification                                       | Notes  |
|------------------------------------------------------------------------------------|----------|----------------------------------------------------------|--------|
| Distillates (petroleum), hydrotreated heavy paraffinic<br>CAS Number: 0064742-54-7 | 50 - 75  | Asp. Tox. 1;H304                                         | [1]    |
| Petroleum distillates, hydrotreated light<br>CAS Number: 0064742-47-8              | 25 - 50  | Asp. Tox. 1;H304                                         | [1]    |
| Isopropyl Alcohol<br>CAS Number: 0000067-63-0                                      | 5 - 10   | Flam. Liq. 2;H225<br>Eye Irrit. 2;H319<br>STOT SE 3;H336 | [1][2] |
| Acetone<br>CAS Number: 0000067-64-1                                                | 5 - 10   | Flam. Liq. 2;H225<br>Eye Irrit. 2;H319<br>STOT SE 3;H336 | [1][2] |
| Butanone<br>CAS Number: 0000078-93-3                                               | 5 - 10   | Flam. Liq. 2;H225<br>Eye Irrit. 2;H319<br>STOT SE 3;H336 | [1][2] |

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

|                                       |       |                                                                                   |        |
|---------------------------------------|-------|-----------------------------------------------------------------------------------|--------|
| Xylene<br>CAS Number: 0001330-20-7    | 1 - 5 | Flam. Liq. 3;H226<br>Acute Tox. 4;H332<br>Acute Tox. 4;H312<br>Skin Irrit. 2;H315 | [1][2] |
| Asphaltum<br>CAS Number: 0012002-43-6 | 1 - 5 | Not Classified                                                                    | [1]    |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Remove and isolate contaminated clothing and shoes.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Wash skin with soap and water.

In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.

Keep victim warm and quiet.

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Eyes

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### Skin

Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

#### Ingestion

If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Overview

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

**Inhalation**

and soreness with possible reversible damage. See section 2 for further details.

**Eyes**

Harmful if inhaled.

Causes serious eye irritation.

**Skin**

Causes mild skin irritation. (Not adopted by US OSHA)

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Do not use: water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Avoid breathing dust / fume / gas / mist / vapors / spray.

#### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Structural firefighters' protective clothing will only provide limited protection.

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Containers may explode when heated.

Many liquids are lighter than water.

Inhalation or contact with material may irritate or burn skin and eyes.

Fire may produce irritating, corrosive and/or toxic gases.

Vapors may cause dizziness or suffocation.

Runoff from fire control may cause pollution.

ERG Guide No.

127

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

**Large Spill:** As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.

Keep unauthorized personnel away.

Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

| CAS No.      | Ingredient        | Source   | Value                                                                     |
|--------------|-------------------|----------|---------------------------------------------------------------------------|
| 0000067-63-0 | Isopropyl Alcohol | OSHA     | TWA 400 ppm (980 mg/m <sup>3</sup> ) STEL 500 ppm                         |
|              |                   | ACGIH    | TWA: 200 ppm STEL: 400 ppm Revised 2003,                                  |
|              |                   | NIOSH    | TWA 400 ppm (980 mg/m <sup>3</sup> ) ST 500 ppm (1225 mg/m <sup>3</sup> ) |
|              |                   | Supplier | No Established Limit                                                      |
| 0000067-64-1 | Acetone           | OSHA     | TWA 1000 ppm (2400 mg/m <sup>3</sup> ) STEL 2400 mg/m <sup>3</sup>        |
|              |                   | ACGIH    | TWA: 500 ppm STEL: 750 ppm                                                |
|              |                   | NIOSH    | 250 ppm (590 mg/m <sup>3</sup> ) TWA                                      |
|              |                   | Supplier | No Established Limit                                                      |
| 0000078-93-3 | Butanone          | OSHA     | TWA 200 ppm (590 mg/m <sup>3</sup> )                                      |
|              |                   | ACGIH    | TWA: 50 ppm STEL: 100 ppm                                                 |
|              |                   | NIOSH    | TWA 200 ppm (590 mg/m <sup>3</sup> ) ST 300 ppm (885 mg/m <sup>3</sup> )  |
|              |                   | Supplier | No Established Limit                                                      |
| 0001330-20-7 | Xylene            | OSHA     | STEL 150 ppm                                                              |
|              |                   | ACGIH    | TWA: 100 ppm STEL: 150 ppm                                                |
|              |                   | NIOSH    | No Established Limit                                                      |
|              |                   | Supplier | No Established Limit                                                      |
| 0012002-43-6 | Asphaltum         | OSHA     | No Established Limit                                                      |

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

|              |                                                        |          |                         |
|--------------|--------------------------------------------------------|----------|-------------------------|
|              |                                                        | ACGIH    | No Established Limit    |
|              |                                                        | NIOSH    | No Established Limit    |
|              |                                                        | Supplier | No Established Limit    |
| 0064742-47-8 | Petroleum distillates, hydrotreated light              | OSHA     | No Established Limit    |
|              |                                                        | ACGIH    | No Established Limit    |
|              |                                                        | NIOSH    | No Established Limit    |
|              |                                                        | Supplier | Recommended 300 ppm PEL |
| 0064742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic | OSHA     | No Established Limit    |
|              |                                                        | ACGIH    | No Established Limit    |
|              |                                                        | NIOSH    | No Established Limit    |
|              |                                                        | Supplier | No Established Limit    |

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH. This product contains no known or suspected carcinogens and is not believed to be carcinogenic.

### Carcinogen Data

| CAS No.      | Ingredient                                             | Source | Value                                                               |
|--------------|--------------------------------------------------------|--------|---------------------------------------------------------------------|
| 0000067-63-0 | Isopropyl Alcohol                                      | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0000067-64-1 | Acetone                                                | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0000078-93-3 | Butanone                                               | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0001330-20-7 | Xylene                                                 | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0012002-43-6 | Asphaltum                                              | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0064742-47-8 | Petroleum distillates, hydrotreated light              | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0064742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic | OSHA   | Select Carcinogen: No                                               |
|              |                                                        | NTP    | Known: No; Suspected: No                                            |
|              |                                                        | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |

### 8.2. Exposure controls

#### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

#### Eyes

Safety glasses with side shields

#### Skin

Wear overalls to keep skin contact to a minimum. Impervious rubber gloves

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

|                                                        |                                                                                                |
|--------------------------------------------------------|------------------------------------------------------------------------------------------------|
| <b>Appearance</b>                                      | Clear to dark Liquid                                                                           |
| <b>Odor</b>                                            | Aromatic                                                                                       |
| <b>Odor threshold</b>                                  | Not Available                                                                                  |
| <b>pH</b>                                              | Not Established                                                                                |
| <b>Melting point / freezing point</b>                  | Not Established                                                                                |
| <b>Initial boiling point and boiling range</b>         | > 93.33 C ( > 200 F)                                                                           |
| <b>Flash Point</b>                                     | 3.88 C (39 F)                                                                                  |
| <b>Evaporation rate (Ether = 1)</b>                    | Less than Bu Acetate                                                                           |
| <b>Flammability (solid, gas)</b>                       | Not Applicable                                                                                 |
| <b>Upper/lower flammability or explosive limits</b>    | <b>Lower Explosive Limit:</b> Not Established<br><b>Upper Explosive Limit:</b> Not Established |
| <b>Vapor pressure (Pa)</b>                             | 51.2 mmHg @20C                                                                                 |
| <b>Vapor Density</b>                                   | > 1                                                                                            |
| <b>Specific Gravity</b>                                | 0.87                                                                                           |
| <b>Solubility in Water</b>                             | Insoluble                                                                                      |
| <b>Partition coefficient n-octanol/water (Log Kow)</b> | Not Measured                                                                                   |
| <b>Auto-ignition temperature</b>                       | Not Established                                                                                |
| <b>Decomposition temperature</b>                       | Not Established                                                                                |
| <b>Viscosity (cSt)</b>                                 | Not Established                                                                                |
| <b>VOC Content</b>                                     | Not Established                                                                                |
| <b>% Volatile</b>                                      | Not available                                                                                  |

#### 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

### 10. Stability and reactivity

#### 10.1. Reactivity

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Excessive heat and open flame.

### 10.5. Incompatible materials

Strong oxidizing agents and acids.

### 10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

| Ingredient                                                            | Oral LD50,<br>mg/kg            | Skin LD50,<br>mg/kg                 | Inhalation<br>Vapor LC50,<br>mg/L/4hr | Inhalation<br>Dust/Mist LC50,<br>mg/L/4hr | Inhalation<br>Gas LC50,<br>ppm |
|-----------------------------------------------------------------------|--------------------------------|-------------------------------------|---------------------------------------|-------------------------------------------|--------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7) | > 5,000.00, Rat - Category: NA | No data available                   | No data available                     | No data available                         | No data available              |
| Petroleum distillates, hydrotreated light - (64742-47-8)              | > 5,000.00, Rat - Category: NA | No data available                   | No data available                     | No data available                         | No data available              |
| Isopropyl Alcohol - (67-63-0)                                         | 4,710.00, Rat - Category: 5    | 12,800.00, Rat - Category: NA       | 72.60, Rat - Category: NA             | No data available                         | No data available              |
| Acetone - (67-64-1)                                                   | 5,800.00, Rat - Category: NA   | 7,426.00, Guinea Pig - Category: NA | 76.00, Rat - Category: NA             | 50.10, Rat - Category: NA                 | No data available              |
| Butanone - (78-93-3)                                                  | 2,737.00, Rat - Category: 5    | 6,480.00, Rabbit - Category: NA     | 32.00, Mouse - Category: NA           | No data available                         | No data available              |
| Xylene - (1330-20-7)                                                  | 4,299.00, Rat - Category: 5    | 1,548.00, Rabbit - Category: 4      | No data available                     | 20.00, Rat - Category: NA                 | 5,000.00, Rat - Category: 4    |
| Asphaltum - (12002-43-6)                                              | No data available              | No data available                   | No data available                     | No data available                         | No data available              |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification                | Category | Hazard Description                                    |
|-------------------------------|----------|-------------------------------------------------------|
| Acute toxicity (oral)         | ---      | Not Applicable                                        |
| Acute toxicity (dermal)       | ---      | Not Applicable                                        |
| Acute toxicity (inhalation)   | 4        | Harmful if inhaled.                                   |
| Skin corrosion/irritation     | 3        | Causes mild skin irritation. (Not adopted by US OSHA) |
| Serious eye damage/irritation | 2        | Causes serious eye irritation.                        |
| Respiratory sensitization     | ---      | Not Applicable                                        |
| Skin sensitization            | ---      | Not Applicable                                        |
| Germ cell mutagenicity        | ---      | Not Applicable                                        |
| Carcinogenicity               | ---      | Not Applicable                                        |
| Reproductive toxicity         | ---      | Not Applicable                                        |
| STOT-single exposure          | ---      | Not Applicable                                        |
| STOT-repeated exposure        | ---      | Not Applicable                                        |
| Aspiration hazard             | ---      | Not Applicable                                        |

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

| Ingredient                                                            | 96 hr LC50 fish, mg/l         | 48 hr EC50 crustacea, mg/l          | ErC50 algae, mg/l                       |
|-----------------------------------------------------------------------|-------------------------------|-------------------------------------|-----------------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7) | 5,000.00, Oncorhynchus mykiss | 1,000.00, Daphnia magna             | Not Available                           |
| Petroleum distillates, hydrotreated light - (64742-47-8)              | 45.00, Pimephales promelas    | 4,720.00, Dendronereides heteropoda | Not Available                           |
| Isopropyl Alcohol - (67-63-0)                                         | 1,400.00, Lepomis macrochirus | 100.00, Daphnia magna               | 100.00 (72 hr), Scenedesmus subspicatus |
| Acetone - (67-64-1)                                                   | 100.00, Pimephales promelas   | 10.00, Daphnia magna                | 20.565 (72 hr), Ulva pertusa            |
| Butanone - (78-93-3)                                                  | 400.00, Cyprinodon variegatus | 520.00, Daphnia magna               | 500.00 (96 hr), Skeletonema costatum    |
| Xylene - (1330-20-7)                                                  | 3.30, Oncorhynchus mykiss     | 8.50, Palaemonetes pugio            | 100.00 (72 hr), Chlorococcales          |
| Asphaltum - (12002-43-6)                                              | Not Available                 | Not Available                       | Not Available                           |

### 12.2. Persistence and degradability

EC/648/2004: For professional or industrial use only, not for sale to the general public. The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

|                                    | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation)    | ICAO/IATA    |
|------------------------------------|---------------------------------------|--------------------------------------|--------------|
| 14.1. UN number                    | UN1263                                | UN1263                               | UN1263       |
| 14.2. UN proper shipping name      | UN1263, Paint, 3, II                  | Paint                                | Paint        |
| 14.3. Transport hazard class(es)   | DOT Hazard Class: 3                   | IMDG: 3<br>Sub Class: Not Applicable | Air Class: 3 |
| 14.4. Packing group                | II                                    | II                                   | II           |
| 14.5. Environmental hazards        |                                       |                                      |              |
| IMDG                               | Marine Pollutant: No;                 |                                      |              |
| 14.6. Special precautions for user | No further information                |                                      |              |

## 15. Regulatory information

|                                    |                                                                                                                   |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Regulatory Overview                | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. |
| Toxic Substance Control Act (TSCA) | All components of this material are either listed or exempt from listing on the TSCA Inventory.                   |
| WHMIS Classification               | B2 D2B                                                                                                            |
| US EPA Tier II Hazards             | Fire: Yes<br>Sudden Release of Pressure: No<br>Reactive: No                                                       |

# Safety Data Sheet

## Restor-A-Finish

SDS Revision Date:

08/20/2014

Immediate (Acute): Yes

Delayed (Chronic): No

### EPCRA 311/312 Chemicals and RQs (lbs):

Acetone ( 5,000.00)

Butanone ( 5,000.00)

Xylene ( 100.00)

### EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### EPCRA 313 Toxic Chemicals:

Ethyl Benzene

Isopropyl Alcohol

Xylene

### Proposition 65 - Carcinogens (>0.0%):

Ethyl Benzene

### Proposition 65 - Developmental Toxins (>0.0%):

Toluene

### Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Toluene

### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### New Jersey RTK Substances (>1%):

Acetone

Butanone

Isopropyl Alcohol

Xylene

### Pennsylvania RTK Substances (>1%):

Acetone

Butanone

Isopropyl Alcohol

Xylene

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our

# **Safety Data Sheet**

## **Restor-A-Finish**

**SDS Revision Date:**

**08/20/2014**

products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

End of Document